

PRICE & PERFORMANCE CHART

"VIRAJ" MAKE NON-CLOG SEWAGE SUBMERSIBLE PUMP

| SR. NO. | MODEL | HP | OUTLET SIZE mm | Solid Size mm | H E A D I N M E T E R | | | | | | | | | | | | | Weight in Kgs. |
|---|------------|------|----------------|---------------|-----------------------------|-------|-------|-------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|----------------------|------------------------|----------------|
| | | | | | 2 | 4 | 6 | 8 | 10 | 12 | 15 | 18 | 20 | 25 | 28 | 32 | 40 | |
| NON- CLOG SEWAGE PUMP -1440 RPM/3 PHASE/AC SUPPLY/50HZ | | | | | | | | | | | | | | | | | | |
| 01 | VNCS 2.0 | 2.0 | 75 | 65 | D I S C H A R G E I N L P M | 1100 | 1050 | 950 | 750 | 650 | 550 | Shut-off Head- 13.5 Mtr. | | | | | 95 | |
| 01 | VNCS 3H | 3.0 | 75 | 65 | | 1100 | 1050 | 950 | 750 | 650 | 550 | Shut-off Head- 13.5 Mtr. | | | | | 95 | |
| 02 | VNCS 3 | 3.0 | 75 | 65 | | 1490 | 1380 | 1150 | 825 | 530 | Shut-Off Head - 12.5 Mtr. | | | | | 95 | | |
| 03 | VNCS 4 | 4.0 | 75/100 | 65 | | 1580 | 1420 | 1250 | 960 | 590 | Shut-Off Head - 13.0 Mtr. | | | | | 125 | | |
| 04 | VNCS 5H | 5.0 | 100 | 75 | | 1450 | 1380 | 1260 | 1100 | 900 | 750 | 250 | Shut-Off Head - 16.5 Mtr. | | | | 135 | |
| 05 | VNCS 5 | 5.0 | 100 | 75 | | 1750 | 1620 | 1435 | 1200 | 860 | 435 | Shut-Off Head - 14.0 Mtr. | | | | | 140 | |
| 06 | VNCS 7.5 | 7.5 | 100 | 80 | | 1890 | 1750 | 1580 | 1390 | 1150 | 780 | 450 | Shut-Off Head - 17.0 Mtr. | | | | 145 | |
| 07 | VNCS 10 | 10.0 | 100 | 80 | | 2180 | 1990 | 1890 | 1750 | 1600 | 1260 | 870 | 250 | Shut-Off Head - 20.0 Mtr. | | | 158 | |
| 08 | VNCS 10M | 10.0 | 100 | 80 | | 2800 | 2360 | 2150 | 1980 | 1200 | 600 | Shut-Off Head - 14.5 Mtr. | | | | | 165 | |
| 09 | VNCS 12.5 | 12.5 | 100 | 80 | | 3450 | 2980 | 2650 | 2360 | 2250 | 1400 | 1100 | 500 | Shut-Off Head - 21.0 Mtr. | | | 170 | |
| 10 | VNCS 15.0 | 15.0 | 100 | 80 | | 3600 | 3350 | 3200 | 3000 | 2800 | 2600 | 2100 | 1650 | 1200 | S.Head - 26.0 Mtr. | | | |
| 11 | VNCS 12.5M | 12.5 | 125 | 80/100 | | 4200 | 3950 | 3250 | 2700 | 1950 | 800 | Shut-Off Head - 14.5 Mtr. | | | | | 279 | |
| 12 | VNCS 15 | 15.0 | 125 | 80 | | 4700 | 4250 | 3900 | 3600 | 3150 | 2000 | 1600 | 1050 | 800 | Shut-Off - 23.5 Mtr. | | 290 | |
| 13 | VNCS 15H | 15.0 | 125 | 80/100 | | 5000 | 4790 | 4450 | 4070 | 3750 | 3450 | 2650 | 1200 | Shut-Off Head - 20.0 Mtr. | | | 295 | |
| 14 | VNCS 20 | 20.0 | 125/150 | 80/100 | | 5200 | 4900 | 4680 | 4200 | 3853 | 3500 | 3350 | 2460 | 1950 | 788 | Shut-Off - 28.0 Mtr. | | 310 |
| 15 | VNCS 20M | 20.0 | 125/150 | 80/100 | | 6500 | 5800 | 5350 | 5100 | 4700 | 4300 | 2860 | 1450 | Shut-Off Head - 22.0 Mtr. | | | 320 | |
| 16 | VNCS 25 | 25.0 | 125/150 | 80/100 | | 7800 | 7100 | 6200 | 5600 | 5200 | 4500 | 4200 | 2860 | 1450 | Shut-Off Head - 25.0 Mtr. | | 335 | |
| 17 | VNCS 30 | 30.0 | 125/150 | 80/100 | | 8100 | 7500 | 6900 | 6200 | 5600 | 5000 | 4400 | 3100 | 2750 | 1100 | Shut-Off - 29.0 Mtr. | | 340 |
| 18 | VNCS 35 | 35.0 | 150 | 80/100 | | 8500 | 7800 | 7200 | 6500 | 6000 | 5400 | 5000 | 4200 | 3500 | 2400 | 1100 | SH- 32 Mtr. | 355 |
| 19 | VNCS-40 | 40.0 | 150/200 | 100 | | | 8500 | 7800 | 7200 | 6700 | 6100 | 5500 | 4700 | 4000 | 2800 | 1800 | 800 | S.H. 37 MT |
| 20 | VNCS-50 | 50.0 | 150/200 | 100 | | 9800 | 8800 | 8200 | 8000 | 7300 | 6500 | 6000 | 5300 | 4000 | 3200 | 2100 | 1200 (S.H.- 42.5 MTR.) | 500 |
| 20 | VNCS-55 | 55.0 | 150/200 | 100 | | 10800 | 9400 | 9050 | 8500 | 7900 | 7100 | 6700 | 5900 | 5000 | 4010 | 2750 | 1400 (S.H.-45 MTR.) | 535 |
| 20 | VNCS-60 | 60.0 | 150/200 | 100 | | | 10800 | 9600 | 8900 | 8200 | 7600 | 7200 | 6400 | 5500 | 4200 | 3100 | 1400 (S.H.-47 MTR.) | 580 |
| 20 | VNCS-65 | 65.0 | 150/200 | 100 | | | 12000 | 11400 | 10800 | 9070 | 8400 | 7800 | 7200 | 6400 | 5000 | 3250 | 1570 (S.H.-48 MTR) | 610 |



NON- CLOG SEWAGE PUMP -2850 RPM/3 PHASE/AC SUPPLY/50HZ

| SR. NO. | MODEL | HP | OUTLET SIZE mm | Solid Size mm | DISCHARGE IN LPM | H E A D I N M E T E R | | | | | | | | | | | | | Weight in Kgs. |
|---------|------------|------|----------------|---------------|------------------|-----------------------|------------|----------------------|---------------------------|---------------------------|---------------------------|-----|---------------------------|------------------|-----|----------------------|-----|-----|----------------|
| | | | | | | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 60 | 65 | 70 | 80 | | |
| 01 | VNCS2-3 | 3.0 | 75 | 20/30 | DISCHARGE IN LPM | 300 | 100 | Shut off - 22.0 mtr. | | | | | | | | | 70 | | |
| 02 | VNCS2-5 | 5.0 | 75 | 20 | | 500 | 300 | 180 | Shut-Off Head - 27.5 Mtr. | | | | | | | | | 80 | |
| 03 | VNCS2-7.5 | 7.5 | 75 | 25 | | 750 | 550 | 400 | 280 | Shut-Off Head - 33.0 Mtr. | | | | | | | 110 | | |
| 04 | VNCS2-10 | 10.0 | 75 | 35 | | 1100 | 980 | 800 | 350 | 200 | Shut-Off Head - 37.0 Mtr. | | | | | 124 | | | |
| 05 | VNCS2-12.5 | 12.5 | 100 | 35 | | 1250 | 1100 | 1000 | 800 | 650 | 500 | 250 | Shut-Off Head - 47.5 Mtr. | | | | 145 | | |
| 06 | VNCS2-15 | 15.0 | 100 | 35 | | 1350 | 1350 | 1250 | 1000 | 900 | 680 | 350 | 180 | S.H. - 52.0 Mtr. | | | 280 | | |
| 07 | VNCS2-20 | 20.0 | 100 | 35 | | | 1500 | 1480 | 1400 | 1250 | 1050 | 800 | 590 | 300 | 200 | Shut-Off - 67.0 Mtr. | | 298 | |



- * All model equipped with Twin- Seal (Bi-directional) , Moisture Sensor , Thermistor Sensor.
- * Also available with Special Material in Product. Std. Pump we are provided all part with C.I.- FG 200 GREAD .
- * With Pump we are provided 10 mt. double sheathed heavy duty water proof / oil proof cable.
- * **WE ARE ALSO PROVIDED ANY SPECIFIC REQUIRED PERFORMANCE IN ABOVE PRODUCT.**